




SUNITRON INC.®

Indoor - Outdoor Computerized LED Signs Since 1986

40 Pippin Rd. Bldg. # 4, Concord Ont. Canada. L4K 4M6
Tel: (905) 660-6888 Fax: (905) 660-8889 Toll Free 1-877-630-8811

MegaVision-255 / 28

- ⇒ Standard 10 mm Pitch.
- ⇒ Indoor / Outdoor Applications
- ⇒ High resolution (240x224 pixel)
- ⇒ LED's x Pixel: 3 (1R, 1G, 1B)
- ⇒ Number of Lines: 28
- ⇒ Characters x Line: 40 (@7x5 Font)
- ⇒ Cabinet Dimension: 100" x 94" x 6"
- ⇒ Character Height (Small): 2.76"
- ⇒ Full matrix display
- ⇒ Superbright daylight visibility
- ⇒ Multistage light sensor (power saver)
- ⇒ Number of LED's: 161280 LED's
- ⇒ Viewing angle: 140°
- ⇒ Display Area: 94" x 88"
- ⇒ Control via VS-Player (IPC)
- ⇒ Weight (approx.): 304 Kg



A Business With A Good Sign - is A Sign of A Good Business®



Technical Specifications MegaVision Series Outdoor Display

Description Module:	160 mm x 160mm Approx.(6.3"x 6.3") Double sided Treated PCB outdoor use.
No. LED's x Pixel:	Three Superbright Diodes (1 Red, 1 Green & 1 Blue)
Pixel Diameter:	Center to center spacing: 10mm.
Viewing angle:	140°
Controller CPU:	Static bias driver (direct drive) for more efficient power distribution.
Brightness (NIT):	≥ 6500 cd/m ² (minimal).
Power consumption:	0.15 watts per pixel maximum high power efficiency.
Estimated lifetime:	LED manufacturer estimates diode life expectancy at 100,000 hours at 30° C Sunitron Inc. will warranty diodes for our standard warranty policy period.
Construction:	Waterproof Steel cabinet black plastic coated with 12.7 mm louvers front face.
Cooling System:	Internal Automatic on /off by force air (fans).
Display matrix:	16 x 16 per modules of 3 LED's per pixel Modules are designed to be "snapped" in and out for quick service.
Features:	Time, Date, Temperature, Text Overlay, Sequencing, Scheduling Preview, Remote Control.
Communication: PC to Sign	Via hardwire (RS232 or RS422) up to 4000 ft. Modems requires telephone line on site Wire-less communication. Operable in TCP/IP for Netware Connectivity
Automatic Dimmer:	Automatic 16 level Light Dimmer (Multi-stage light "Power Saver" sensor and life to display). 128 Level Programmable Light sensor via software
Standard Warranty:	5-years service depot warranty on all parts and labour, including on line direct support toll free # 1-877-630-8811.
Technical Support:	10 year technical support for software upgrading when available .
Operation Software:	Windows base software (Size, Position, Brightness Control)
Power requirement:	110/120Vac service, internal switch powers supply cUL 5 Vdc. With automatic circuit for over voltage protection shot-/off.
Electrical cable:	To be determinate by electrical contractor according to CSA standard.
Colour Depth:	16 bit Colour
Colour Displayed	468.7 Billions
Waterproof Level:	International Protection Rating: IP 65 6: Dust tight (No ingress of dust; complete protection against contact) 5: Water jets (Water projected by a nozzle against enclosure from any direction shall have no harmful effects)